



SEKURBLOK

- **Robust:** High strength synthetic housing, offering long durability.
- **Safe:** for maximum loads of 140 Kg reducing the impact force below 6kN.
- **Swivel ring:** to avoid tangles and improve the operation of the equipment.
- **Drop indicator:** in case of fall the green line turns red, indicating the user's fall.
- **Certified for work in ATEX** explosive atmospheres.

Norm	EN 360 ATEX 94/9/CE, EN 13463-1 EN 13463-5, II 2 G c T6				
Length (m)	7,5	10	15	20	30
Weight (kg)	3,57	3,77	6,9	7,45	12,8
Stopping distance (m)	1,35	1,35	1,4	1,4	1,5
Height (mm)	263	263	320	320	396
Length (mm)	172	172	224	224	280
Width (mm)	87	87	94	94	109
Load (Kg)	140				
Static resistance	15 kN				
Impact force	< 6 kN				
Lifetime	Unlimited				

Materials

Cable Galvanized Steel (4,5mm)

Housing Synthetic

CONNECTORES SEKURBLOK

Inferior connector 976	
Opening	20mm
Material	Steel
Resistance	23 kN
Closure	Automatic
Rotatory	Yes
Fall indicator	Yes

Superior connector 981	
Opening	18mm
Material	Steel
Resistance	25 kN
Closure	Thread
Rotatory	No
Fall indicator	No