

**ANCHORAGE**

# **ARO SLING TUBULAR**



## **POLYAMIDE WEBBING LOOPS**

Polyamide sling perfect to make a stopover or to extend an anchor point. The product is supplied in different colors to suit lengths.

Custom lengths are also available upon request. Available in black.

Width of tape: 15 mm

Breaking strength: 23 kN

High quality product completely developed and produced in Italy.

### **Usage activities**

CLIMBING

MOUNTAINEERING

CANYONING

CAVING



SNOW & ICE

SCAFFOLDING AND TRESTELS

ROOF AND INCLINED PLANES

FIREBRIGADES AND CIVIL PROTECTION

# ITEM CODES

| Item        | Standards                                   | Material  |  (g) |  (kN) | Size | Colour          | A (mm) | Hole diameter (mm) | Notes |
|-------------|---|-----------|---|--|------|-----------------|--------|--------------------|-------|
| 271T030R0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 28  | 22   | 30   | Red<br>Black    | 30 cm  | /                  |       |
| 271T030N0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 28  | 22   | 30   | Black           | 30 cm  | /                  |       |
| 271T060G0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 45  | 22   | 60   | Black<br>Green  | 60 cm  | /                  |       |
| 271T060N0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 45  | 22   | 60   | Black           | 60 cm  | /                  |       |
| 271T080O0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 60  | 22   | 80   | Black<br>Orange | 80 cm  | /                  |       |
| 271T080N0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 60  | 22   | 80   | Black           | 80 cm  | /                  |       |
| 271T120R0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 90  | 22   | 120  | Red<br>Black    | 120 cm | /                  |       |
| 271T120N0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 90  | 22   | 120  | Black           | 120 cm | /                  |       |
| 271T150Y0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 115   | 22   | 150  | Black<br>Yellow | 150 cm | /                  |       |
| 271T180O0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 135   | 22   | 180  | Black<br>Orange | 180 cm | /                  |       |
| 271T180N0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 135   | 22   | 180  | Black           | 180 cm | /                  |       |
| 271T250R0KK | EN 795/B<br>EN 354<br>EN 566<br>UIAA<br>EAC | Polyamide | 160   | 22   | 250  | Red<br>Black    | 250 cm | /                  |       |